User Manual - Dahua 2X14AWG-U

---

1. Introduction

The **Dahua 2X14AWG-U** is an **unshielded fire alarm cable**, UL-certified, designed for use in **fire detection systems, emergency lighting, ventilation control, communication, and fire suppression equipment**. Its **solid or stranded copper conductor** ensures reliable and durable electrical conductivity.

This cable is ideal for **commercial, industrial, and residential applications**, offering **high-temperature resistance and flame-retardant properties** to enhance safety in critical installations.

---

2. Key Features

- **Solid or stranded copper conductor** for increased durability and efficiency.
- **UL-certified** for fire alarm systems.
- **PVC insulation and outer jacket** for high flame and heat resistance.
- **Weather-resistant**: Suitable for outdoor exposure.
- **High voltage resistance**: Tested at **2500V DC/2s**.
- **Flexible and adaptable design**, customizable for specific requirements.

---

3. Installation

3.1. Prerequisites

Before installation, ensure you have:

- A suitable installation area, free from electrical interference.
- Wire cutting and fastening tools.

- Conduits and trays for additional protection if required.
- Connection to compatible fire detection and control systems.

3.2. Installation Procedure

1. **Carefully unroll the cable** to avoid bends or damage.
2. **Determine the cable routing**, ensuring efficient installation.
3. **Secure the cable** within conduits or trays as necessary.
4. **Make secure connections** using certified terminals.
5. **Verify continuity and insulation** before powering the system.

---

4. Usage and Maintenance

- **Regular Inspection**: Check cable integrity every six months.
- **Proper Cleaning**: Prevent dust and debris accumulation on connectors.
- **Resistance Testing**: Perform periodic continuity and insulation tests.
- **Preventive Replacement**: Replace damaged or visibly deteriorated cables.

---

5. Troubleshooting

Issue	Possible Cause	Solution
No signal in the system	Disconnected or damaged cable	Check connections and continuity
Insulation failure	Excessive heat exposure	Replace affected sections and reinforce protection

Overheating	Circuit overload	Verify system compatibility

---

6. Technical Specifications

- **Model**: 2X14AWG-U
- **Conductor Type**: 1/1.63±0.02 mm bare copper
- **Maximum Resistance**: 8.45 Ω/KM at 20°C
- **Insulation**: Black and red PVC
- **Insulation Thickness**: Average 0.38 mm / Minimum 0.33 mm
- **Outer Jacket**: UL105°C PVC-55P red PVC
- **Outer Diameter**: 6.3 ± 0.3 mm
- **Jacket Thickness**: Average 0.58 mm / Minimum 0.46 mm
- **Maximum Temperature**: 105°C (221°F)
- **Voltage Resistance Test**: 2500V DC / 2s
- **Minimum Insulation Resistance**: 100MΩ/KFT at 15.6°C
- **Flame Retardant Rating**: VW-1
- **Certification**: UL Listed
- **Packaging Method**: 305-meter roll

---

7. Warranty and Support

For technical assistance and updates, refer to Dahua’s official documentation or contact authorized technical support.