SignalMaster™ Plus

available in:



Federal Signal…pointing the way in LED directional lighting.
The SignalMaster Plus directs traffic with its eye-catching chase sequence of light patterns. The SignalMaster Plus is available in six- and eight-lamp configurations. Each LED module contains 3 high-powered amber LEDs that draw only 0.25 Amps while producing high intensity wide-angle warning signals.

Paired with a SignalMaster controller (required for operation, sold separately), systems can do a variety of warning signals including: left, right, center-out and flashing warning.

Built to meet the demands of many applications.
The SignalMaster Plus is designed to accommodate a full scope of applications. A sturdy aluminum extrusion houses individually sealed LED modules with a clear polycarbonate lens. A mounting bolt slot on the rear of the extrusion is designed to accommodate a wide variety of mounting configurations.

A versatile solution for directional warning.
A selection of internal and external mounting brackets makes SignalMaster Plus ideal for many applications including municipal, utility, construction, public safety and tow and recovery. The SignalMaster Plus is backed by a three-year warranty.



330104



330105

Features

- Low Amp draw.
- Internal or external mounting.
- Water/corrosion resistant black aluminum housing.
- Variety of specialty mounting brackets available.
- Ideal for many different applications.
- Individually sealed LED modules with wide-angle lens.

5 Year Warranty

How to Order

Specify SignalMaster Plus Model

SMLED-PLS-6 28", (6) LED modules, 30-ft cable, clear lens with amber LEDs

SMLED-PLS-8 37", (8) LED modules, 50-ft cable, clear lens with amber LEDs

Order SignalMaster Mounts (sold separately)

320310 Flush (vertical surface mount)

320320 Lightbar or rear deck mount

320220 System mount

320340 Universal mount

320250 Foot adapter mount

Order SignalMaster Controller (sold separately)

330104 Standard controller

331105 Full-featured controller

	28"	37"
Specifications		
Volts	12 or 24	12 or 24
Current Draw	.25 Amp draw per module 1.5 Amps (6 head unit)	.25 Amp draw per module 2 Amps (8 head unit)
Physical Specifications		
Height	1.8 in (4.6 cm)	1.8 in (4.6 cm)
Length	28 in (71.7 cm)	37 in (94.7 cm)
Width	2.25 in (5.76 cm)	2.25 in (5.76 cm)
Ship Weight		
	12.2 lbs (5.5 kg)	14.5 lbs (6.6 kg)



320310



320330



320350



320320



320340

FEDERAL SIGNAL

2645 Federal Signal Drive, University Park, IL 60484
Tel.: (800) 264-3578 • Fax: (800) 682-8022
www.fedsig.com

SignalMaster is a trademark of Federal Signal Corporation.

©2010 Federal Signal Corporation.