- **LKV488Mini Specifications**

Items		Specifications
Power Supply	Voltage/Current	Micro USB power supply (5V/1A)
	Power consumption	TX < 4.5W, RX < 3.5W
HDMI Performance and Interface	HDMI version	HDMI 2.0
	HDCP version	HDCP 1.4/HDCP 2.2
	Max transmission rate	18Gbps
	Resolution supported	3840x2160@24/30/50/60Hz (YUV 4:4:4, YUV 4:2:2 and RGB),1080P@50/60Hz, 720P@50/60Hz, 1920x1200@60Hz
	Input and output TMDS signal	0.7~1.2Vp-p（TMDS）
	Input and output DDC signal	5Vp-p（TTL）
Transmission	Wi-Fi Frequency bands	5.18-5.24 GHz
	Transmission distance	≤ 20m
Transmission	Latency	130~200ms
	Connection types	One to one
	SSID pairing	Supported
Protection Level	ESD protection	1a Contact discharge level 3 1b Air discharge level 3 Standard: IEC61000-4-2
Operating Environment	Working temperature	-20~50℃
	Storage temperature	-30~70℃
	Humidity (no condensation)	0~90% RH
Physical Properties	Dimension	TX: 40.2(W) * 230(L) * 15.0(H)mm RX: 40.2(W) * 230(L) * 15.0(H)mm
	Color	Black
	Material	ABS
	Net weight	TX: 58g; RX: 54g