DHI-ESL-BLP02-80

LCD 80W Power Supply



- Power the LCD.
- Convenient use.
- Small size and portable.

Introduction

The power supply is used to power the LCD. It features easy use, small size and portable, which can be used at any time.

Features

Small Size
Small size and portable.

Convenient Use
Power the LCD screen at any time.

Scene

LCD screen.

Technical Specification

Performance

Model	DHI-ESL-BLP02-80
Input Voltage	Global Width Voltage: AC:100-240V/180-260V/47-63Hz,135-373VDC
Input Current	0.8A/230 VAC
Certificate	CE RoHs FCC IP67
Output Voltage	12 VDC
Output Current	6.7 A
Input Plug	European standard

General

Bare Machine Dimensions	169 mm × 49 mm × 34 mm (6.65" × 1.93" × 1.34")
Net Weight	0.65 kg (1.43 lb)
Gross Weight	0.95 kg (2.09 lb)
Packaging	12 Pieces/Carton
Inner Box Dimensions	258 mm × 127 mm × 121 mm (10.16" × 5.00" × 4.76")
Outer Box Dimensions	500 mm × 350 mm × 250 mm (19.69" × 13.78" × 9.84")
Packaging Method	Carton

Environmental Constraints

Temperature	–25 °C to 65 °C (–13 °F to 149 °F)
Humidity	20%-90% RH

Ordering Information

Type	Model	Description
ESL-B Series	DHI-ESL-BLP02-80	LCD 80W Power Supply

Rev 002.000 © 2024 Dahua. All rights reserved. Design and specifications are subject to change without notice.
The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.