DHI-PHEIA1.8-TH

Indoor Fine Pixel Pitch LED



Features :

· Three-in-one integrated design of control board.
· Support Front/Rear maintenance.
· Tool free disassembly of Hub board.
· Hardwired wireless design.
· Support GOB encapsulation technology (customizable)
· Dot by dot calibration ensures color richness and brightness uniformity.



Technical Specification

Model	
Model	DHI-PHEIA1.8-TH

Parameters	
Pixel Pitch	1.86mm
Pixel Configuration	1R1G1B
LED Type	SMD1515
Brightness (Max)	800 nit
Color Temperature	2000K-9500K
Viewing Angle	H140° / V140°
Pixel Density	288,906 dots/m²
Module Size	320mm×160mm
Module Resolution	172x86 dots
Cabinet Size	W640mm×H480mm×D54mm
Cabinet Resolution (W×H)	344×258 dots
Cabinet Weight	6.5 kg ± 0.1
Cabinet Material	Die-casting Aluminum

Operating Temperature/ Humidity	-10℃~+45℃/10~80%RH
Storage Temperature/ Humidity	-20℃~+55℃/10~80%RH
IP Rating	Front IP30/Rear IP30
Aspect Ratio	4:3
Gray Scale	12-14 bit
Contrast Ratio	5000:1
Refresh Rate	3840Hz
Input Voltage	AC 100~220V (+/-10%)
Input Power (max)	650 W/m²
Input Power (Avg)	210 W/m²
Installation	Wall Mounted/Floor Mounted
Maintenance	Front/Rear Maintenance
Lamp Lifespan	≥100,000 H
Signal Transmission Distance	CAT5 Cable (L≤100m), multi-mode fiber (L≤300m), single mode fiber (L≤10km)

Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice.
The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.