H_2xHDMI2.0+2xDP1.2 Input Card

Input Card



Specifications

Appearance







Specifications

This card can be installed into the slots from I-1 to I-8 of the H15 and H15 Enhanced only.

Two group inputs, each group with 1x HDMI 2.0 and 1x DP1.2 connector

Only one connector of each group can be used each time.

Set to use which connector on the Web page. The default option is HDMI 2.0 connector.

Does not support interlaced signal input.

2x HDMI 2.0

- Backward compatible with HDMI 1.4 and HDMI 1.3
- Supports the maximum resolution of 3840×2160@60Hz.
- HDCP 2.2 compliant
- Custom resolutions:

  Max. width: 4092 pixels (4092×2261@60Hz)

  Max. height: 4095 pixels (2188×4095@60Hz)

2x DP 1.2

- Backward compatible with DP 1.1
- Supports the maximum resolution of 4096×2160@60Hz or 8192×1080@60Hz.

- HDCP 2.2 compliant
- Custom resolutions:

  Max. width: 8192 pixels (8192×1146@60Hz)

  Max. height: 4095 pixels (2188×4095@60Hz)

Status LEDs

- On: The input source is accessed normally.
- Off: No input source is accessed or the input source is abnormal.

Copyright © 2023 Xi'an NovaStar Tech Co., Ltd. All Rights Reserved.

No part of this document may be copied, reproduced, extracted or transmitted in any form or by any means without the prior written consent of Xi'an NovaStar Tech Co., Ltd.

Trademark

NOVASTAR is a trademark of Xi'an NovaStar Tech Co., Ltd.

Statement

Thank you for choosing NovaStar's product. This document is intended to help you understand and use the product. For accuracy and reliability, NovaStar may make improvements and/or changes to this document at any time and without notice. If you experience any problems in use or have any suggestions, please contact us via the contact information given in this document. We will do our best to solve any issues, as well as evaluate and implement any suggestions.

Official website
www.novastar.tech

Technical support
support@novastar.tech